

theRonda S360 KNX AP BK

Item no.: 2089552



Presence and motion detectors
Ceiling installation indoor

Description

- Passive infra-red presence detector KNX for ceiling installation
- Circular detection area 360°, Ø 8 m, (50 m²) at mounting height 3 m
- 2 channels light and 2 channels presence
- Mixed light measurement
- 2 light channels C1, C2
- Switching operation or constant light control with standby function (orientation light)
- Switching mode with dimmable lighting
- Choice of fully or semi-automatic
- Brightness switching value or set point value can be set in lux by using parameters, the object or via remote control
- Teach-in of the brightness switching value or the set point value
- Reduction of time delay when present briefly (short-term presence)
- Manual override by telegram or remote control
- 2 presence channels C4, C5, individually configurable
- Switch-on delay and time delay configurable
- Setting the room correction factor for brightness measurement comparison
- Adjustable sensitivity
- Test mode for checking function and detection area
- Scenes
- Parallel switching of multiple presence detectors (Master/Slave or Master/Master)
- User remote control «theSenda S» (option)
- Management remote control «SendoPro 868-A» (option)
- Installation remote control «theSenda P» (option)



Technical data

theRonda S360 KNX AP BK	
Installation height	2 - 4 m
Minimum height	1.7 m

theRonda S360 KNX AP BK	
Detection angle	360°
Type of connection	KNX bus terminal

Subject to technical changes and misprints
additional information at: www.theben.de/product/2089552
The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

theRonda S360 KNX AP BK

Item no.: 2089552




Technical data

theRonda S360 KNX AP BK		theRonda S360 KNX AP BK	
Installation type	Ceiling installation, Surface mounted	Switch-on delay presence	10 s - 30 min / inactive
Light switch-off delay	30 s - 60 min	Ambient temperature	-15°C ... 50°C
Lamp types	Energy saving lamps, fluorescent lamps, Incandescent/halogen lamps, LEDs	Detection range	50 m² (ø 8 m)
Light measurement	Mixed light measurement	Colour	Black
Presence switch-off delay	10 s - 120 min	Type of protection	IP 54
		GWP Cradle-to-Gate (A1-A3)	4.11 kg CO ₂ eq
		GWP Cradle-to-Grave (A1-C4)	14.08 kg CO ₂ eq

Detection range for planning applications at a temperature of 21 °C

Mounting height (A)	Sitting (S)	Diagonally (T)	Head on to (R)
2 m	5 m² 2.5 m	38 m² 7 m	5 m² 2.5 m
2.5 m	7 m² 3 m	38 m² 7 m	7 m² 3 m
3 m	13 m² 4 m	50 m² 8 m	13 m² 4 m
3.5 m	13 m² 4 m	50 m² 8 m	13 m² 4 m
4 m	13 m² 4 m	64 m² 9 m	13 m² 4 m




theRonda S360 KNX AP BK

Item no.: 2089552

theben

Scale drawings



Accessories

theSenda P

Item no.: 9070910



theSenda S

Item no.: 9070911




theSenda B

Item no.: 9070985




QuickSafe

Item no.: 9070531



QuickSafe

Item no.: 9070531



Subject to technical changes and misprints

additional information at: www.theben.de/product/2089552

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

05/08/2026

Page 3 of 3