



N 528/41 UNIVERSAL DIMMER S300 SLAVE DIMMER, 300 VA

Similar to image

Technical data:		
Design type		lighting
Type, explanations		Universal Dimmer
Design of the product		dimming actuator
Type of mounting		modular installation device
Number of analog outputs		1
Number of pitch units for width		3
Adjustable real power	W	20 ... 500
Operating voltage rated value	V	230 ... 230
Product component - integrated / Bus coupling - Extension input - LED		No Yes No
Bus system / can be used / EIB/KNX		No
Bus system / usable / RF bus system		No
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Product function		

• Parallel operation		No
• direct operation		No
Extension de produit / en option / puissance additionnelle		No
Operating frequency		
• rated value	Hz	60 ... 50
Type of load		universal
Protection class IP		IP20
Design		N
Electrical output protection against overload and short-circuiting		yes

Certificates/approvals:

**General Product
Approval**

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1528-1AB41/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1528-1AB41

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 1, 2013