

N 502/02 COMBINED SWITCH ACTUAT 8X BE AC/DC 12-230V,
8X BA AC 230V, 16 A AC1



Similar to image

Technical data:

Type of display / LED		Yes
Type of mounting		modular installation device
Switching capacity real power	W	3,680
Breaking capacity current	A	16
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Number of digital inputs		8
Number of pitch units for width		8
Number of switching outputs / maximum		8
Operating current / rated value	A	16
Operating voltage		
• rated value	V	230 ... 230
Product function / direct operation		Yes
Product component / integrated / Bus coupling		Yes
Protection class IP		IP20

Certificates/approvals:

**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1502-1AB02/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1502-1AB02

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 12, 2013